NSN 4720-01-137-5328

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-137-5328

Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
2.120 inches
Minimum Inside Bending Radius:
22.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Socket nickel alloy 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
1200.0 pourido por oquaro mon
First End Swivel Action Capability:
First End Swivel Action Capability:
First End Swivel Action Capability: Not included
First End Swivel Action Capability: Not included Layer Composition And Location:
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure:
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.875 inches 1st end
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle:
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 37.0 degrees 1st end
First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100 Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 1.875 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition:

NSN 4720-01-137-5328

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0