## NSN 4720-01-137-8126

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-137-8126

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.420 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 350.0 degrees fahrenheit single response
Outside Diameter:
0.560 inches
Minimum Inside Bending Radius:
4.620 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

16.250 inches

## NSN 4720-01-137-8126

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0