## NSN 4720-01-137-8210

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-137-8210

Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
2.120 inches
Minimum Inside Bending Radius:
22.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Socket nickel alloy 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
12000.0 pounds per square inch
12000.0 pounds per square inch First End Swivel Action Capability:
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:  3000.0 pounds per square inch
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.875 inches 1st end
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.875 inches 1st end  Seat Angle:
12000.0 pounds per square inch  First End Swivel Action Capability:  Not included  Layer Composition And Location:  1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure:  3000.0 pounds per square inch  Thread Size:  1.875 inches 1st end  Seat Angle:  37.0 degrees 1st end
12000.0 pounds per square inch  First End Swivel Action Capability: Not included  Layer Composition And Location: 1st layer spiral interlocked corrosion resistant steel err-100  Maximum Operating Pressure: 3000.0 pounds per square inch  Thread Size: 1.875 inches 1st end  Seat Angle: 37.0 degrees 1st end  Inside Surface Condition:

## NSN 4720-01-137-8210

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0