Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-138-1485



Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Tempurature Rating:

-32.0 degrees celsius and 52.0 degrees celsius single response

Outside Diameter:

2.125 inches

Quick Disconnect Size:

1.500 inches 2nd end

End Application:

Support equipment, c-5 aircraft

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided cotton cord and outer layer molded rubber, synthetic

Hydrostatic Test Pressure:

150.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and ozone resistant

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

360.000 inches

Special Features:

Weapon system essential

Specification Data:

81349-mil-h-370 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4720-01-138-1485

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

