

View Online at <https://aerobasegroup.com/nsn/4720-01-138-8986>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

2.000 inches

**Unable To Decode:**

Unable to decode or unable to decode

**First End Fitting Specification/std Data:**

Ms27025-2 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Second End Fitting Specification/std Data:**

Ms27021-2 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Quick Disconnect Size:**

2.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Connection Type:**

Internal quick disconnect 1st end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

500.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, natural err-100 or outer layer molded rubber, synthetic err-100

**Maximum Operating Pressure:**

110.0 pounds per square inch

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Ozone resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

240.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Banding clamps for hose fittings cres per a-a-52506

**Media For Which Designed:**

Water single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0