

View Online at <https://aerobasegroup.com/nsn/4720-01-138-8986>

Cross Sectional Shape:

Round

Inside Diameter:

2.000 inches

Unable To Decode:

Unable to decode or unable to decode

First End Fitting Specification/std Data:

Ms27025-2 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Ms27021-2 standard (includes industry or association standards, individual manufactureer standards, etc.).

Quick Disconnect Size:

2.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Connection Type:

Internal quick disconnect 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, natural err-100 or outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

110.0 pounds per square inch

Hydrostatic Test Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

240.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Banding clamps for hose fittings cres per a-a-52506

Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0