Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-139-1855

Cross	Sectional	Shape:
-------	-----------	--------

Round

Thread Class:

3b 1st end

## Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.500 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.870 inches

Minimum Inside Bending Radius:

#### 7.000 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Reusable end fittings

### **Burst Test Pressure:**

14000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

3500.0 pounds per square inch

#### Thread Size:

0.875 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

7000.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Oil resistant and weatherproof

## Inside Surface Condition:

Smooth

## Measuring Method And Length:

16.000 inches

AeroBase Group

## Media For Which Designed:

Fuel/oil, hydrocarbon single response

## Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A542a0