

View Online at <https://aerobasegroup.com/nsn/4720-01-139-3190>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b and 2a 1st end

**Thread Direction:**

Right-hand and right-hand 1st end

**Inside Diameter:**

0.125 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.470 inches 2nd end

**Outside Diameter:**

0.410 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Exterior Color:**

Black

**Connection Style:**

Inverted flare 1st end

**Bolt Hole Diameter:**

0.400 inches 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Unthreaded fluid passage bolt 2nd end

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

2000.0 pounds per square inch

**Thread Size:**

0.375 inches and 0.625 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.000 inches

**Special Features:**

Furnished w/one mounting bracket

**Media For Which Designed:**

Brake fluid, nonmineral oil single response

**Thread Series Designator:**

Unf and unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0