## NSN 4720-01-139-6355

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-139-6355

Cross Sectional Shape:
Round
Inside Diameter:
0.395 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.715 inches
Minimum Inside Bending Radius:
5.750 inches
Hose Or Tubing Specification/std Data:
Mil-h-38360 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Burst Test Pressure:
10500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire err-100
Maximum Operating Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Specification Data:
Mil-h-38360 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Filg:
A542a0
Mil-std (military Standard):
Mil-h-38360 spec.