

View Online at <https://aerobasegroup.com/nsn/4720-01-139-6355>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.395 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.715 inches

**Minimum Inside Bending Radius:**

5.750 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-38360 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Burst Test Pressure:**

10500.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.000 inches

**Special Features:**

Inner conveying tube material-plastic, polytetrafluoroethylene

**Specification Data:**

Mil-h-38360 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-38360 spec.