NSN 4720-01-140-4633

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-140-4633

-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
1.031 inches
Minimum Inside Bending Radius:
7.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
20000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally laid corrosion resistant steel wire err-100
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches

NSN 4720-01-140-4633

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0