NSN 4720-01-143-0955

Unj 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-143-0955

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 1.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.800 inches |
| Minimum Inside Bending Radius: |
| 7.500 inches |
| Connection Style: |
| Swivel nut, flareless 2nd end |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Burst Test Pressure: |
| 3000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided steel wire |
| Maximum Operating Pressure: |
| 750.0 pounds per square inch |
| Thread Size: |
| 1.875 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Flow Angle: |
| 72.0 degrees 2nd end |
| Inside Surface Condition: |
| Convoluted |
| Measuring Method And Length: |
| 10.875 inches and 11.125 inches |
| Thread Series Designator: |

NSN 4720-01-143-0955

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0