## NSN 4720-01-143-1091

Unj 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-143-1091

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3a 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.500 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.800 inches  |
| Minimum Inside Bending Radius:  |
| 7.500 inches  |
| Connection Style:   |
| Flared 2nd end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external tube 2nd end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Thready Qty Per Inch (tpi):   |
| 12 2nd end  |
| Burst Test Pressure:  |
| 3000.0 pounds per square inch   |
| Layer Composition And Location:   |
| Outer layer braided steel wire  |
| Maximum Operating Pressure:   |
| 750.0 pounds per square inch  |
| Thread Size:  |
| 1.875 inches 2nd end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Flow Angle:   |
| 72.0 degrees 2nd end  |
| Inside Surface Condition:   |
| Convoluted  |
| Measuring Method And Length:  |
| 10.875 inches and 11.125 inches   |
| Thread Series Designator:   |

## NSN 4720-01-143-1091

Nonmetallic Hose Assembly - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0