NSN 4720-01-143-2873

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-143-2873

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.750 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.030 inches |
| Minimum Inside Bending Radius: |
| 7.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided textile yarn and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Hydrostatic Test Pressure: |
| 500.0 pounds per square inch |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 474.000 inches |
| Media For Which Designed: |
| Air and fuel/oil, hydrocarbon and water single response |
| Thread Series Designator |

Npt 1st end

NSN 4720-01-143-2873

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0