Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-144-3020

| Cross Sectional Shape: | |
|---------------------------------------|--------------------------------------------------------------------------------------------------|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.500 inches | |
| Tempurature Rating: | |
| 40.0 degrees fahrenheit and 250.0 | degrees fahrenheit single response |
| Outside Diameter: | |
| 0.920 inches | |
| Minimum Inside Bending Radius: | |
| 6.500 inches | |
| Connection Style: | |
| Swivel nut flare 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Burst Test Pressure: | |
| 2000.0 pounds per square inch | |
| ayer Composition And Location: | |
| st layer braided textile yarn and 2nd | d layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric |
| Maximum Operating Pressure: | |
| 750.0 pounds per square inch | |
| Thread Size: | |
| 0.875 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 1st end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 43.000 inches | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single respons | e |
| Thread Series Designator: | |
| Unf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |

NSN 4720-01-144-3020

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

