Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-144-3421

Round         Round         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.500 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimum Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread diternal hose 1st end         Thready Qty Per Inch (tpi):         11/12 1st end         Burst Test Pressure:         800.0 pounds per square inch         Layer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         200.0 pounds per square inch         Heride Surface Condition:         Smoth         Measuring Method And Length:         96.000 inches         Media For Which Designed:         Water single response         Thread Size         Modia For Which Designed:     <	Creas Sectional Shaney
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.500 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimum Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thready Qty Per Inch (tpi):         11-1/2 1st end         Baser         Boo.0 pounds per square inch         Layer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         10.00 pou	Cross Sectional Shape:
Right-hand 1st end         Inside Diameter:         0.500 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimum Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal hose 1st end         Thready Qty Per Inch (tpi):         11-1/2 1st end         Buoy pounds per square inch         Layer Composition And Location:         13t layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         20.00 pounds per square inch         Hread Size:         1.000 inches 1st end         Hydrostati Test Pressure:         400.0 pounds per square inch         Hread Size:         1.000 inches 1st end         Hydrostati Test Pressure:         400.0 pounds per square inch         Hiside Surface Condition:         Smooth         Measuring Method And Length:	
Inside Diameter:         0.500 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimum Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal hose 1st end         Thready Guy Per Inch (tpl):         11-1/2 1st end         Bust Test Pressure:         800.0 pounds per square inch         Layer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         400.0 pounds per square inch         Herd Size:         1.000 inches 1st end         Hydrostatic Test Pressure:         400.0 pounds per square inch         Herd Size:         1.000 inches 1st end         Hydrostatic Test Pressure:         400.0 pounds per square inch         Herd Size:         1.000 inches 1st end         Hydrostatic Test Pressure:	
0.500 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimum Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal hose 1st end         Thready Qty Per Inch (tpi):         11-1/2 1st end         Bust         Bust Test Pressure:         800.0 pounds per square inch         Layer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         400.0 pounds per square inch	-
Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.650 inches         Minimun Inside Bending Radius:         5.000 inches         Exterior Color:         Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal hose 1st end         Harren Rating:         800.0 pounds per square inch         Hayer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         400.0 pounds per square inch         Heasuring Method And Length: <td< td=""><td></td></td<>	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single responseOutside Diameter:0.650 inchesMinimun Inside Bending Radius:5.000 inchesExterior Color:BlackConnection Style:Swivel nut, gasket seal 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal hose 1st endThreade dinternal hose 1st endEust Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchHread Size:1.000 inches 1st endHydrostatic Test Pressure:200.0 pounds per square inchHinde Size:1.000 inches 1st endHydrostatic Test Pressure:200.0 pounds per square inchHinde Size:1.000 inches 1st endHydrostatic Test Pressure:200.0 pounds per square inchHinde Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMedia For Which Designed:Vater single responseThread Series Designator:Nin 1st endShelf Life:	
Outside Diameter:0.650 inchesMinimum Inside Bending Radius:5.000 inchesExterior Color:BlackConnection Style:Swivel nut, gasket seal 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal hose 1st endThready Qty Per Inch (tpi):11-1/2 1st endBurst Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchHread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchEntread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchEntread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchEntread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchHasuring Method And Length:96.000 inchesMedia For Which Designed:Vater single responseThread Series Designator:Nh 1st endShelf Life:	
0.650 inches Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Busst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Inread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 300.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Thread Size: 1.000 inches Media For Which Designed: Vater single response Thread Series Designator: Nh 1st end Shelf Life:	
Minimum Inside Bending Radius: 5.000 inches Exterior Color: Black Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal hose 1st end Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure: 400.0 pounds per square inch Hydrostatic Test Pressure: 400.0 pounds per square inch Hydrostatic Test Pressure: 6000 inches 1st end Hydrostatic Test Pressure: 96.000 inches Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
<ul> <li>S.000 inches</li> <li>Exterior Color:</li> <li>Black</li> <li>Connection Style:</li> <li>Swivel nut, gasket seal 1st end</li> <li>End Connection Design:</li> <li>Straight 1st end</li> <li>Connection Type:</li> <li>Threaded internal hose 1st end</li> <li>Thready Qty Per Inch (tpi):</li> <li>11-1/2 1st end</li> <li>Burst Test Pressure:</li> <li>800.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>1st layer braided cotton cord and outer layer molded rubber, synthetic</li> <li>Maximum Operating Pressure:</li> <li>200.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Enstreise Pressure:</li> <li>200.0 pounds per square inch</li> <li>Bread Size:</li> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Hist And</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>400.0 pounds</li></ul>	
Exterior Color: Black Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Straight 1st end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	-
Black         Connection Style:         Swivel nut, gasket seal 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal hose 1st end         Thready Qty Per Inch (tpi):         11-1/2 1st end         Burst Test Pressure:         800.0 pounds per square inch         Layer Composition And Location:         1st layer braided cotton cord and outer layer molded rubber, synthetic         Maximum Operating Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         200.0 pounds per square inch         Hydrostatic Test Pressure:         400.0 pounds per square inch         Hydrostatic Test Pressure:         400.0 pounds per square inch         Hydrostatic Test Pressure:         96.000 inches         Measuring Method And Length:         96.000 inches         Media For Which Designed:         Water single response         Thread Series Designator:         Nh 1st end         Shelf Life:	
Connection Style: Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Swivel nut, gasket seal 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
End Connection Design:Straight 1st endConnection Type:Threaded internal hose 1st endThready Qty Per Inch (tpi):11-1/2 1st endBurst Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchHydrostatic Test Pressure:400.0 pounds per square inchBinside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	-
Straight 1st end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	-
Connection Type:Threaded internal hose 1st endThready Qty Per Inch (tpi):11-1/2 1st endBurst Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	-
Threaded internal hose 1st end Thready Qty Per Inch (tpi): 11-1/2 1st end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	-
Thready Qty Per Inch (tpi):11-1/2 1st endBurst Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMater single responseThread Size:Nh 1st endShelf Life:	
<ul> <li>11-1/2 1st end</li> <li>Burst Test Pressure:</li> <li>800.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>1st layer braided cotton cord and outer layer molded rubber, synthetic</li> <li>Maximum Operating Pressure:</li> <li>200.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>96.000 inches</li> <li>Media For Which Designed:</li> <li>Water single response</li> <li>Thread Series Designator:</li> <li>Nh 1st end</li> <li>Shelf Life:</li> </ul>	
Burst Test Pressure:800.0 pounds per square inchLayer Composition And Location:1st layer braided cotton cord and outer layer molded rubber, syntheticMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMetia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	
<ul> <li>800.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>1st layer braided cotton cord and outer layer molded rubber, synthetic</li> <li>Maximum Operating Pressure:</li> <li>200.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>96.000 inches</li> <li>Media For Which Designed:</li> <li>Water single response</li> <li>Thread Series Designator:</li> <li>Nh 1st end</li> <li>Shelf Life:</li> </ul>	
Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
<ul> <li>1st layer braided cotton cord and outer layer molded rubber, synthetic</li> <li>Maximum Operating Pressure:</li> <li>200.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>96.000 inches</li> <li>Media For Which Designed:</li> <li>Water single response</li> <li>Thread Series Designator:</li> <li>Nh 1st end</li> <li>Shelf Life:</li> </ul>	
Maximum Operating Pressure:200.0 pounds per square inchThread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	
200.0 pounds per square inch Thread Size: 1.000 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Thread Size:1.000 inches 1st endHydrostatic Test Pressure:400.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:96.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	
<ul> <li>1.000 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>400.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>96.000 inches</li> <li>Media For Which Designed:</li> <li>Water single response</li> <li>Thread Series Designator:</li> <li>Nh 1st end</li> <li>Shelf Life:</li> </ul>	
Hydrostatic Test Pressure: 400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
400.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Inside Surface Condition: Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	-
Smooth Measuring Method And Length: 96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Measuring Method And Length:96.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 1st endShelf Life:	
96.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Media For Which Designed: Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Water single response Thread Series Designator: Nh 1st end Shelf Life:	
Thread Series Designator: Nh 1st end Shelf Life:	-
Nh 1st end Shelf Life:	
Shelf Life:	-
N/a	
	N/a

## NSN 4720-01-144-3421

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0