

View Online at <https://aerobasegroup.com/nsn/4720-01-145-4820>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

2.266 inches

Minimum Inside Bending Radius:

13.250 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided fabric and 2nd layer rubber impregnated braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

350.0 pounds per square inch

Thread Size:

2.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

700.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.000 inches excluding end fittings

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0