Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-146-4123

| ross Sectional Shape: |
|--|
| bund |
| nread Class: |
| o 1st end |
| nread Direction: |
| ght-hand 1st end |
| side Diameter: |
| 688 inches |
| empurature Rating: |
| 5.0 degrees fahrenheit and 450.0 degrees fahrenheit single response |
| utside Diameter: |
| 219 inches |
| inimum Inside Bending Radius: |
| 750 inches |
| onnection Style: |
| wivel nut, flareless 1st end |
| nd Connection Design: |
| raight 1st end |
| onnection Type: |
| nreaded internal tube 1st end |
| eatures Provided: |
| eusable end fittings |
| nready Qty Per Inch (tpi): |
| 2 1st end |
| urst Test Pressure: |
| 2000.0 pounds per square inch |
| ayer Composition And Location: |
| st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubb |
| loroprene |
| aximum Operating Pressure: |
| 000.0 pounds per square inch |
| nread Size: |
| 062 inches 1st end |
| eat Angle: |
| 3.0 degrees 1st end |
| ydrostatic Test Pressure: |
| 000.0 pounds per square inch |
| uter Covering Environmental Protection: |
| prasion resistant and oil resistant and oxidation resistant |
| side Surface Condition: |
| nooth |
| easuring Method And Length: |
| 3.125 inches working |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0