

View Online at <https://aerobasegroup.com/nsn/4720-01-146-7932>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.367 inches and 0.398 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.812 inches and 0.875 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Black

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external hose 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

1.188 inches 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and mildew resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon and water, fresh and water, salt single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-24135 spec.