NSN 4720-01-149-4974

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-149-4974

| Cross Sectional Shape: | | | | | | |
|--|--|--|--|--|--|--|
| Round | | | | | | |
| Thread Class: | | | | | | |
| 2b 1st end | | | | | | |
| Thread Direction: | | | | | | |
| Right-hand 1st end | | | | | | |
| Inside Diameter: | | | | | | |
| 0.500 inches | | | | | | |
| Outside Diameter: | | | | | | |
| 0.900 inches | | | | | | |
| Exterior Color: | | | | | | |
| Black | | | | | | |
| Connection Style: | | | | | | |
| Swivel nut flare 1st end | | | | | | |
| End Connection Design: | | | | | | |
| Straight 2nd end | | | | | | |
| Connection Type: | | | | | | |
| Threaded internal tube 1st end | | | | | | |
| Burst Test Pressure: | | | | | | |
| 7000.0 pounds per square inch | | | | | | |
| Layer Composition And Location: | | | | | | |
| 1st layer braided cotton cord and outer layer molded rubber, synthetic | | | | | | |
| Maximum Operating Pressure: | | | | | | |
| 1750.0 pounds per square inch | | | | | | |
| Thread Size: | | | | | | |
| 0.750 inches 1st end | | | | | | |
| Seat Angle: | | | | | | |
| 37.0 degrees 1st end | | | | | | |
| Hydrostatic Test Pressure: | | | | | | |
| 3500.0 pounds per square inch | | | | | | |
| Inside Surface Condition: | | | | | | |
| Smooth | | | | | | |
| Measuring Method And Length: | | | | | | |
| 22.000 inches | | | | | | |
| Special Features: | | | | | | |
| Furnished w/one adapter st thd 0.750-16 unf by 0.500-15 nptf | | | | | | |
| Media For Which Designed: | | | | | | |
| Air single response | | | | | | |
| Thread Series Designator: | | | | | | |
| Unf 1st end | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 4720-01-149-4974

Nonmetallic Hose Assembly - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0