NSN 4720-01-151-2593

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-151-2593

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.870 inches
Minimum Inside Bending Radius:
7.000 inches
Connection Style:
Nut assembly with gasket 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.000 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and water single response
Thread Series Designator:

Unf 1st end

NSN 4720-01-151-2593

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0