## NSN 4720-01-151-2604

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-151-2604 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.830 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 3500.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric **Maximum Operating Pressure:** 875.0 pounds per square inch **Thread Size:** 0.875 inches 2nd end Seat Angle: 45.0 degrees 2nd end Flow Angle: 45.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 42.375 inches Media For Which Designed:

**Thread Series Designator:** 

Fuel/oil, hydrocarbon single response

Unf 2nd end

## NSN 4720-01-151-2604

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0