## NSN 4720-01-152-9204

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-152-9204 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 1.560 inches **Minimum Inside Bending Radius:** 3.500 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 1.625 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch **Outer Covering Environmental Protection:** 

**Inside Surface Condition:** 

Corrosion resistant

Convoluted

**Measuring Method And Length:** 

9.000 inches

## NSN 4720-01-152-9204

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	<b>Designator:</b>
--------	--------	--------------------

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0