NSN 4720-01-154-3183

Cross Sectional Shape:

23.625 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-154-3183

Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.199 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.320 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
50000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:

NSN 4720-01-154-3183

Nonmetallic Hose Assembly - Page 2 of 2



	•		
I hread	Series	Designator:	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0