NSN 4720-01-154-6335

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-154-6335

Cross Sectional Shape:

| Round |
|--|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.875 inches |
| Tempurature Rating: |
| -100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.031 inches |
| Minimum Inside Bending Radius: |
| 9.000 inches |
| Connection Style: |
| Swivel, plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 800.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided bronze wire |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 1.000 inches 1st end |
| Outer Covering Environmental Protection: |
| Fuel resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 12.000 inches |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4720-01-154-6335

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0