Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-156-0539

Cross Sectional Shape:	
Round Fhread Class:	
3b 1st end	
Fhread Direction:	
Right-hand 1st end	
nside Diameter:	
0.310 inches	
Fempurature Rating:	
40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Dutside Diameter:	
0.680 inches	
Minimum Inside Bending Radius:	
1.000 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
0000.0 pounds per square inch	
Layer Composition And Location:	
st layer braided textile yarn and 2nd layer braided corrosion resistant steel wire and	d outer layer rubber impregnated braided fabric
Maximum Operating Pressure:	
2250.0 pounds per square inch	
Thread Size:	
0.562 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Flow Angle:	
00.0 degrees 2nd end	
nside Surface Condition:	
Smooth	
Neasuring Method And Length:	
4.000 inches excluding end fittings	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Fhread Series Designator:	
Jnf 2nd end	
Shelf Life:	
V/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0