

View Online at <https://aerobasegroup.com/nsn/4720-01-157-4109>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.190 inches

**Temperature Rating:**

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.520 inches

**Minimum Inside Bending Radius:**

0.750 inches

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

24 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyester cord and 2nd layer braided wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.170 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0