NSN 4720-01-157-4320

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-157-4320

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.762 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
End Application:
Hemtt family (heavy expanded mobility tactical trucks); 2320-01-097-0260 hiab crane (hemtt)
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal pipe 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
32.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4720-01-157-4320

Nonmetallic Hose Assembly - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A542a0