NSN 4720-01-159-7691

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-159-7691

2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.458 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Red
Connection Style:
Swivel nut, inverted flare 2nd end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 2nd end
Second End Relationship With First End:
Not identical
Burst Test Pressure:
200.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer braided cotton cord
Maximum Operating Pressure:
50.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
100.0 pounds per square inch

NSN 4720-01-159-7691

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
18.250 inches
Second End Swivel Action Capability:
Not included
Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Air single response
Thread Series Designator:
Uns 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0