NSN 4720-01-160-1071

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-1071

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.312 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Connection Style: |
| Swivel nut, flareless 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.437 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 12000.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 10.000 inches working |
| Thread Series Designator: |
| Unjf 2nd end |

NSN 4720-01-160-1071

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0