Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-5775

ross Sectional Shape:	
ound	
hread Direction:	
ight-hand 1st end	
nside Diameter:	
.750 inches	
empurature Rating:	
0.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
utside Diameter:	
219 inches	
xterior Color:	
lack	
onnection Style:	
iverted flare 1st end	
nd Connection Design:	
traight 1st end	
onnection Type:	
hreaded external pipe 1st end	
urst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer molded rubber, synthetic and 2nd layer braided steel wire and 3rd layer molded rubbe	۶r
laximum Operating Pressure:	
250.0 pounds per square inch	
hread Size:	
.750 inches 1st end	
eat Angle:	
0.0 degrees 1st end	
ydrostatic Test Pressure:	
500.0 pounds per square inch	
side Surface Condition:	
mooth	
leasuring Method And Length:	
.000 inches working	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	
hread Series Designator:	
pt 1st end	
helf Life:	
/a	
nit Of Measure:	

NSN 4720-01-160-5775

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

