## NSN 4720-01-160-5776

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-5776

Round			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.250 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response			
Outside Diameter:			
0.580 inches			
Minimum Inside Bending Radius:			
1.750 inches			
Connection Style:			
Inverted flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded external pipe 1st end			
Features Provided:			
Reusable end fittings			
Burst Test Pressure:			
2000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided corrosion resistant steel wire and outer layer rubber impregnated fabric			
Maximum Operating Pressure:			
500.0 pounds per square inch			
Thread Size:			
0.250 inches 1st end			
Seat Angle:			
30.0 degrees 1st end			
Hydrostatic Test Pressure:			
1000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Oil resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			

Thread Series Designator:

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water single response

12.000 inches

Npt 1st end

## NSN 4720-01-160-5776

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0