## NSN 4720-01-160-6713

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-6713

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.713 inches
Minimum Inside Bending Radius:
5.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive and reusable end fittings
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.000 inches

## NSN 4720-01-160-6713

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Alcohol, ethyl and hydraulic fluid, water base and fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A542a0