NSN 4720-01-160-8204

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.344 inches

Tempurature Rating:

Outside Diameter:

0.547 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-8204

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Minimum Inside Bending Radius:					
2.500 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Unthreaded external hose 2nd end					
Burst Test Pressure:					
6000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
1000.0 pounds per square inch					
Thread Size:					
0.562 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
3000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Fuel resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
23.510 inches					
Inside Diameter Hose Accommodated:					
0.344 inches 2nd end					
Special Features:					
An anodized aluminum prebent tube is the second end of this assembly; 0.350 inch end offset					

NSN 4720-01-160-8204

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Fuel/oil, hydrocarbon single response and hydraulic fluid, silicate-ester base single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0