NSN 4720-01-160-8204

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.344 inches

Tempurature Rating:

Outside Diameter:

0.547 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-160-8204

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

| Minimum Inside Bending Radius: |
|---|
| 2.500 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Unthreaded external hose 2nd end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Fuel resistant and oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 23.510 inches |
| Inside Diameter Hose Accommodated: |
| 0.344 inches 2nd end |
| Special Features: |
| An anodized aluminum prebent tube is the second end of this assembly; 0.350 inch end offset |
| |
| |
| |

NSN 4720-01-160-8204

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designed: |
|---------------------------|
|---------------------------|

Fuel/oil, hydrocarbon single response and hydraulic fluid, silicate-ester base single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0