NSN 4720-01-161-5109

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-161-5109

0.298 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
0.565 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Connection Style:			
Swivel nut, flareless 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
14000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.562 inches 2nd end			
Seat Angle:			
12.0 degrees 2nd end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Flow Angle:			
45.0 degrees 2nd end			
Outer Covering Environmental Protection:			
Fuel resistant and solvent resistant and vibration resistant and heat resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
17.750 inches working			

NSN 4720-01-161-5109

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0