

View Online at <https://aerobasegroup.com/nsn/4720-01-162-5113>

Cross Sectional Shape:

Round

Thread Class:

3a 2nd end

Thread Direction:

Right-hand 2nd end

Inside Diameter:

0.250 inches

Temperature Rating:

-55.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.547 inches

Minimum Inside Bending Radius:

1.000 inches

Connection Style:

Flared 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 2nd end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated fabric

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.500 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

9.000 inches

Special Features:

1st end has a tube assembly with a internally thd connection

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0