## NSN 4720-01-162-8964

**Cross Sectional Shape:** 

96906-ms8006 government standard

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-162-8964

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.343 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 2nd end
12.0 degrees 2nd end  Hydrostatic Test Pressure:
Hydrostatic Test Pressure:
Hydrostatic Test Pressure: 3000.0 pounds per square inch
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle:
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition:
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length:
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 10.000 inches working

## NSN 4720-01-162-8964

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0