

View Online at <https://aerobasegroup.com/nsn/4720-01-162-8965>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand all ends

Inside Diameter:

0.298 inches

Temperature Rating:

-65.0 degrees fahrenheit and 275.0 degrees fahrenheit 1st response

Outside Diameter:

0.540 inches

Minimum Inside Bending Radius:

2.500 inches

Connection Style:

Swivel nut, flareless all ends

End Fitting Component And Material:

Body stainless steel all ends

Connection Type:

Threaded internal tube all ends

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches all ends

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.125 inches

Product Name:

Hose assembly, hi-press; flareless, lightweight

Special Features:

Fep polytetrafluoroethylene, metal band and fep polytetrafluoroethylene at junction of end fitting assembly; item includes chafe guard

Media For Which Designed:

Hydraulic fluid 2nd response

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0