Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-163-1088

Round

Thread Class:

2b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.875 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

### **Outside Diameter:**

1.210 inches

Minimum Inside Bending Radius:

#### 3.500 inches

**Exterior Color:** 

Black

#### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

## Thready Qty Per Inch (tpi):

14 1st end

#### **Burst Test Pressure:**

1600.0 pounds per square inch

### Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord

### Maximum Operating Pressure:

400.0 pounds per square inch

#### Thread Size:

1.250 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

800.0 pounds per square inch

## Inside Surface Condition:

Smooth

## Measuring Method And Length:

42.500 inches

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0