## NSN 4720-01-163-4683

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-163-4683

| Cross Sectional Shape:  |
|---|
| Round   |
| Inside Diameter:  |
| 2.000 inches  |
| Tempurature Rating:   |
| 212.0 degrees fahrenheit single response  |
| Outside Diameter:   |
| 2.094 inches  |
| Quick Disconnect Size:  |
| 1.969 inches 2nd end  |
| Connection Style:   |
| Cam or lever (external) 2nd end   |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Internal quick disconnect 1st end   |
| Burst Test Pressure:  |
| 300.0 pounds per square inch  |
| Layer Composition And Location:   |
| 1st layer rubber impregnated braided fabric and 2nd layer helix copper coil and outer layer rubber impregnated braided fabric |
| Hydrostatic Test Pressure:  |
| 100.0 pounds per square inch  |
| Outer Covering Environmental Protection:  |
| Age resistant and oil resistant and ozone resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 120.000 inches  |
| Special Markings:   |
| Blue longitudinal stripe to denote potable water only   |
| Specification Or Standard:  |
| A grade and a style and 2 class   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A542a0  |