## NSN 4720-01-163-6617

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-163-6617

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.344 inches and 0.375 inches
Minimum Inside Bending Radius:
1.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
27 1st end
Burst Test Pressure:
1600.0 pounds per square inch
Layer Composition And Location:
1st layer braided rayon cord and outer layer molded rubber, neoprene
Maximum Operating Pressure:
400.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.938 inches working and 24.062 inches working
Special Features:
Electrical insulation sleeving p/n 8034668-56 fscm 18876
Thread Series Designator:

Uns 1st end

## NSN 4720-01-163-6617

Nonmetallic Hose Assembly - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0