NSN 4720-01-164-0343

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-01-164-0343 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.391 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.605 inches |
| Minimum Inside Bending Radius: |
| 2.880 inches |
| Connection Style: |
| Swivel nut, flareless 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings and electrostatic discharge capability |
| Burst Test Pressure: |
| 14000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Heat resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

11.000 inches working

Thread Series Designator:

Unjf 1st end

NSN 4720-01-164-0343

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0