## NSN 4720-01-164-7039

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-164-7039

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.125 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response                                  |
| Outside Diameter:  |
| 0.438 inches   |
| Minimum Inside Bending Radius:   |
| 2.000 inches   |
| Exterior Color:  |
| Black  |
| Connection Style:  |
| Inverted flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Unthreaded fluid passage bolt 2nd end  |
| Burst Test Pressure:   |
| 5000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 1250.0 pounds per square inch  |
| Thread Size:   |
| 0.375 inches 1st end   |
| Seat Angle:  |
| 30.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 2500.0 pounds per square inch  |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 17.500 inches  |
| Special Features:  |
| Item has a mounting bracket located 8.000 in. From first end   |

**Media For Which Designed:**Brake fluid, nonmineral oil single response

## NSN 4720-01-164-7039

Nonmetallic Hose Assembly - Page 2 of 2



Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0