## NSN 4720-01-165-5881

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-165-5881

Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.200 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer rubber impregnated braided steel wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Mildew resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.250 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon and grease and hydraulic fluid single response
Thread Series Designator:
Npt 1st end
Specification Data:
96214-843989-1 professional/industrial association specification
Shelf Life:

N/a

## NSN 4720-01-165-5881

Nonmetallic Hose Assembly - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A542a0