Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-166-5367

Served Schemel Schemer	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
.375 inches	
empurature Rating:	
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Dutside Diameter:	
.781 inches	
/inimum Inside Bending Radius:	
.000 inches	
Connection Style:	
Swivel, plain 2nd end	
Ind Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Burst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided steel wire and outer layer molded rubber	
laximum Operating Pressure:	
250.0 pounds per square inch	
hread Size:	
.375 inches 1st end	
Seat Angle:	
0.0 degrees 1st end	
lydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Dil resistant and weatherproof	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
6.000 inches	
ledia For Which Designed:	
lydraulic fluid single response	
hread Series Designator:	
Iptf 2nd end	
Shelf Life:	
I/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0