Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-167-2809

Round <b>Thread</b>	Sectional Shape: Direction:
Thread	Direction:
	Direction:
Right-ha	
•	and 1st end
	Diameter:
1.375 in	
	rature Rating:
	egrees fahrenheit and 250.0 degrees fahrenheit single response
	e Diameter:
1.750 in	
	m Inside Bending Radius:
10.500 i	inches
Connec	ction Style:
Inverted	flare 1st end
End Co	nnection Design:
Straight	1st end
Connec	ction Type:
Threade	ed external pipe 1st end
Burst T	est Pressure:
2000.0	pounds per square inch
Layer C	Composition And Location:
1st laye	r braided fiber and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximu	um Operating Pressure:
500.0 p <sup>,</sup>	ounds per square inch
Thread	Size:
1.500 in	iches 1st end
Seat Ar	ngle:
30.0 de	grees 1st end
Inside \$	Surface Condition:
Smooth	
Measur	ing Method And Length:
158.000	) inches
Media F	For Which Designed:
Fuel/oil,	hydrocarbon single response
Thread	Series Designator:
Nptf 1st	end
Shelf Li	ife:
N/a	
Unit Of	Measure:
Demilit	arization:
No	

## NSN 4720-01-167-2809

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

