NSN 4720-01-167-7052

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-167-7052

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.594 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1260.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and outer layer braided fiber
Maximum Operating Pressure:
315.0 pounds per square inch
Thread Size:
0.437 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
630.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches
Media For Which Designed:
Water single response
Thread Series Designator:

Unf 1st end

NSN 4720-01-167-7052

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0