Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-168-1083

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
	0 degrees fahrenheit single response
Minimum Inside Bending Radius	
4.000 inches	
Connection Style:	
Swivel nut with loose or integral cli	nch sleeve 1st end
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
4500.0 pounds per square inch	
Layer Composition And Location	n:
1st layer braided textile yarn and 2	2nd layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:	
1125.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
180.000 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single respo	nse
Thread Series Designator:	
Unf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-01-168-1083

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

