Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-168-1692

Cross S	Sectional Shape:
Round	
Thread	Direction:
Right-ha	and 1st end
Inside [Diameter:
0.250 in	ches
Tempu	rature Rating:
-40.0 de	egrees fahrenheit and 200.0 degrees fahrenheit single response
Outside	e Diameter:
0.620 in	ches
Minimu	m Inside Bending Radius:
3.000 in	ches
Exterio	r Color:
Black	
Connec	ction Style:
Inverted	I flare 1st end
End Co	nnection Design:
Straight	1st end
Connec	ction Type:
Threade	ed external pipe 1st end
Burst T	est Pressure:
ا 1260.0	pounds per square inch
Layer C	Composition And Location:
1st laye	r braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, neoprene
Maximu	Im Operating Pressure:
315.0 po	ounds per square inch
Thread	Size:
0.250 in	iches 1st end
Seat Ar	ngle:
30.0 deg	grees 1st end
Hydros	tatic Test Pressure:
630.0 po	ounds per square inch
Inside S	Surface Condition:
Smooth	
Measur	ing Method And Length:
180.000) inches
Media F	For Which Designed:
Air singl	le response
Thread	Series Designator:
Npt 1st	end
Shelf Li	ife:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0